

## SM kabl tipa Mini Breakout sa 12 vlakna za unutrašnju montažu, G.657, I-V(ZN=B)H

---

Proizvođač: Reichle & De-Massari  
Kataloška oznaka: R512712  
Mini Breakout I-V(ZN=B)H

Jed.mere: m  
PDV: 20 %

Cena: zvati  
Garancija: 5 godina



---

The mini breakout cable is the ideal fiber to the desk solution for direct connector fitting. Due to its compact design it is easy to install, where space is limited it is perfect and economic solution. The 900µm tight buffers are individually colored and surrounded by glass yarns. Sheath: LSZH, green.

Fiber: singlemode (SM) E9/125

Standardisation : ITU-T G.657 IEC 60793-2-50:2004, B 1.3 IEC 60794-1-2 E1; IEC 60794-1-2 E11; IEC 60794-1-2 E3; IEC 60794-1-2 F1; IEC 60332-1; IEC 61034; IEC 60754-2

Cable class : Mini Breakout

Cable design : I-V(ZN=B)H

Number of fibers / conductors : 12

Cable jacket material : LSZH

Cable jacket characteristics : cable, metal-free ; zero-halogen

Cable protection : no protection

Cable overall diameter : 6.5 mm

Conductor type : tight buffer

Fiber / conductor diameter : E9/125 µm, G.657.A1, A2 + B2 (OS1, OS2)

Fiber type : Singlemode (SM)

Color : green

Length (meter) : 2000